

M133WK

13.3" Intel® Core™ i5-8265U Ruggedized Tablet



KEY FEATURES

- Intel® Core™ i5-8265U Whiskey Lake processor ruggedized tablet
- 13.3" 1920 x 1080 IPS wide viewing angle LED Panel
- Magnesium alloy housing with all-around elastomeric rubber
- Built-in kickstand usable as carrying handle (indefinitely adjustable)
- IP65 waterproof and dustproof
- Optical bonding technology
- TPM 2.0

INTRODUCTION

Winmate M133 Series Ultra Rugged Tablet is built for performance and durability in the toughest environments. Featuring a 13.3" sunlight-readable IPS display with optical bonding, it offers exceptional clarity and usability. Its magnesium alloy housing with elastomeric rubber ensures rugged protection, while IP65-rated waterproof and dustproof design enhances reliability. Equipped with a built-in adjustable kickstand, fanless cooling, and TPM 2.0 for security, the M133 Series is ideal for industrial applications and field operations demanding durability and efficiency.

SPECIFICATIONS

Display

Resolution	1920x1080	Size	13.3 inches
Contrast Ratio	1000:1	Panel Brightness	500.0 nits
View Angles	89,89,89,89	Type	Projected Capacitive Multi Touch
Bonding	Optical Bonding for Sunlight Viewability		

System Specification

Processor	Intel Core i5-8265U 1.6GHz (up to 3.9GHz)	Memory	4GB SODIMM DDR4-2400 8GB SODIMM DDR4-2400 (Optional) 16GB SODIMM DDR4-2400 (Optional)
Storage	Storage 1: 1 x 128GB M.2 SSD Additional storage available with SDXC card slot Storage 1 up to 1x 1TB M.2 SSD (Optional) Storage 2 up to 1x 1TB M.2 SSD (Optional)	Security	Trusted Platform Module (TPM) 2.0 Kensington Lock
Operating System	Windows 10 IoT Enterprise LTSC (64 bit) Windows 11 IoT Enterprise LTSC (64 bit) (Optional)	WLAN	Support
BT	Support	WWAN	4G LTE (Optional)
GNSS	GPS/GLONASS (Optional)		

Mechanical

Dimension	338.20 x 239.82 x 33.80 mm	Weight	2.2kg (w/ kickstand)
Cooling System	Fanless Design		

IO Ports

USB Port	4 x USB 3.0 Type A, 1 x USB 3.0 Type C	SD Card Slot	1 x SDXC Slot
----------	--	--------------	---------------

Operating Humidity	30% to 80% RH, non-condensing	Operating Temperature	-10°C to 50°C (14°F to 122°F)
Storage Temperature	-20°C to 60°C (-4°F to 140°F)	Shock	MIL-STD-810G Method 516.6 Procedure I
Vibration	MIL-STD-810G Method 514.6 Procedure I	IP rating	IP65
Drop	MIL-STD-810G Method 516.6, 4 ft		

Certification

Certification	CE, FCC
---------------	---------

Security Function

Kensington Lock	Kensington Lock Support
-----------------	-------------------------

Control

Button	1 x Power, 1 x menu, 2 x volume key 3 x Programmable Function Keys
--------	---

Camera

Rear Camera	1 x 8MP Rear Camera with auto-focus and LED light (Optional)
-------------	--


Power

Battery	15.4V, typ. 5900 mAh Li-Polymer Battery (4S1P)	Battery Operating Time	More than 10 hours (BAPCo TabletMark v3)
Power Rating	19V DC	Adapter	100-240V, 50-60Hz / 19V DC

Accessory

Accessory	Adapter and Power Cord Standard Battery Stylus Stand with Integrated Kickstand	Optional Accessory	Vehicle Charger (Optional) Battery Charger (Optional) Desk Docking (Optional) Handle (Optional)
-----------	---	--------------------	--

DIMENSIONS UNIT:MM



NOTE

- 1. Total usable memory will be less dependent upon actual system configuration.
- 2. TPM 2.0 is available upon request.
- 3. Length measurements do not include protrusions. Weight varies with options.
- 4. Measured at dimming LCD brightness. Varies depending on the usage conditions, or when an external device is attached.
- 5. This is a simplified drawing and some components are not marked in detail.
- 6. The product shown in this datasheet is a standard model. For diagrams that contain customized or optional I/O, please contact the Winmate Sales Team for more information.