

# Storage SuperServer SSG-221E-NE324R

2U front-loading all-flash storage server with 24 E3.S NVMe drives and PCIe 5.0



## Key Applications

Software-defined Storage, In-Memory Computing, Data Intensive HPC, Private & Hybrid Cloud, NVMe Over Fabrics Solution,


## Key Features

- Dual Socket E (LGA-4677) 5th/4th Generation Intel® Xeon® Scalable processors. Up to 350W TDP.;
- Supports 32 DIMMs with 2DPC, up to 8TB memory capacity with 32 DIMMs of 256GB 3DS RDIMM DDR5-5600 ECC memory;
- Two PCIe 5.0 x16 slots & two PCIe x8 slots and two AIOM connectors (OCP 3.0 SFF compliant);
- 24x hot-swap E3.S (7.5mm) NVMe drive bays;
- Redundant Titanium 2000W Power Supplies;




|                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Form Factor              | 2U Rackmount<br>Enclosure: 438.4 x 89.8 x 789.9mm (17.2" x 3.5" x 30.8")<br>Package: 673.1 x 254 x 1098.55mm (26.5" x 10" x 43.25")                                                                                                                                                                                                                                                                                                                                                 |
| Processor                | Dual Socket E (LGA-4677)<br>5th Gen Intel® Xeon® / 4th Gen Intel® Xeon® Scalable processors                                                                                                                                                                                                                                                                                                                                                                                         |
| System Memory            | Slot Count: 32 DIMM slots<br>Max Memory (2DPC): Up to 8TB 5600MT/s ECC DDR5 RDIMM/LRDIMM                                                                                                                                                                                                                                                                                                                                                                                            |
| Drive Bays Configuration | Default: Total 24 bays <ul style="list-style-type: none"> <li>• 24 front hot-swap E3.S 1T NVMe drive bays</li> </ul> M.2: 2 M.2 NVMe/SATA slots (M-key 2280/22110)                                                                                                                                                                                                                                                                                                                  |
| Expansion Slots          | Default <ul style="list-style-type: none"> <li>• 4 PCIe 5.0 x8 FHHL slots</li> <li>• 2 PCIe 5.0 x16 AIOM slots (OCP 3.0 compatible)</li> </ul> Option A <ul style="list-style-type: none"> <li>• 2 PCIe 5.0 x8 FHHL slots</li> <li>• 1 PCIe 5.0 x16 FHHL slot</li> <li>• 2 PCIe 5.0 x16 AIOM slots (OCP 3.0 compatible)</li> </ul> Option B <ul style="list-style-type: none"> <li>• 2 PCIe 5.0 x16 FHHL slots</li> <li>• 2 PCIe 5.0 x16 AIOM slots (OCP 3.0 compatible)</li> </ul> |
| On-Board Devices         | Chipset: Intel® C741<br>Network Connectivity: Via AIOM                                                                                                                                                                                                                                                                                                                                                                                                                              |

(Front View – System)



(Rear View – System)



|                       |                                                                                                                                                                                                                                                                                                                         |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| System Cooling        | Fans: Up to 4 Heavy Duty 8cm Fan(s)<br>Air Shroud: 2 Air Shrouds                                                                                                                                                                                                                                                        |
| Power Supply          | 1x 2000W Redundant Titanium Level (96%) power supply                                                                                                                                                                                                                                                                    |
| Management            | SuperCloud Composer®; Supermicro Server Manager (SSM); Supermicro Update Manager (SUM); Supermicro SuperDoctor® 5 (SD5); Super Diagnostics Offline (SDO); Supermicro Thin-Agent Service (TAS); SuperServer Automation Assistant (SAA) New!                                                                              |
| PC Health Monitoring  | CPU: 7 Phase-switching voltage regulator<br>Monitors for CPU Cores, Chipset Voltages, Memory<br>FAN: Fans with tachometer monitoring<br>Pulse Width Modulated (PWM) fan connectors<br>Status monitor for speed control<br>Temperature: Monitoring for CPU and chassis environment<br>Thermal Control for fan connectors |
| Dimensions and Weight | Weight: Gross Weight: 77 lbs (34.93 kg)<br>Net Weight: 55 lbs (24.95 kg)<br>Available Color: Silver                                                                                                                                                                                                                     |
| Operating Environment | RoHS Compliant<br>Operating Temperature: 10°C to 35°C (50°F to 95°F)<br>Non-operating Temperature: -40°C to 60°C (-40°F to 140°F)<br>Operating Relative Humidity: 8% to 90% (Non-Condensing)<br>Non-operating Relative Humidity: 5% to 95% (Non-Condensing)                                                             |
| Motherboard           | <a href="#">Super X13DSF-A</a>                                                                                                                                                                                                                                                                                          |
| Chassis               | CSE-236E3-R2K08P                                                                                                                                                                                                                                                                                                        |